

Q8 T 2300 CVT 10W-30

Exceptional synthetic Tractor Continuous Variable Transmission Fluid

Description

Q8 T 2300 CVT 10W-30 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 T 2300 CVT 10W-30 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

Applications

Q8 T 2300 CVT 10W-30 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant. The oil meets the requirements of almost all OEMs.

Benefits

- Superior viscosity retention providing smoothless CVT operation.
- Best-in-class oxidation stability.
- Superior frictional properties for smooth brake operation.
- Superior response of hydraulic components.
- Maximum compatibility with conventional elastomers.

Specifications, recommendations and approvals

AGCO	CVT ML 200	Valtra	G2-B10 (XT-60+)
API	GL-4	ZF	TE-ML 06B
Case New Holland	MAT 3525	ZF	TE-ML 06D
Case New Holland	MAT 3540	ZF	TE-ML 06E
Caterpillar	SATO	ZF	TE-ML 06F
Claas	CVT	ZF	TE-ML 06H
Fendt	Vario	ZF	TE-ML 06L
John Deere	JDM J20C	ZF	TE-ML 06M
Massey Ferguson	CMS M 1145	ZF	TE-ML 06R
Valtra	G2-08 (XT-60)	ZF	TE-ML 06S

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,858
Viscosity Grade	SAE J306	-	75W-85
Viscosity Grade	SAE J300	-	10W-30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	70.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.8
Viscosity Index	D 2270	-	165
Brookfield Viscosity, -26 °C	D 2983	Pa.s	3,4
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	208

The figures above are not a specification. They are typical figures obtained within production tolerances.