



Designation	Capacity in litres	Dimensions in cm				Reference weight in kg	
		a	b	c	d		
Easy Mobil 440 Standard Station, Cematic 3000 12 V pump	440	118	80	71	28		
The set of 4 stations Easy Mobil 440 Standard	440				28	35	10985
Easy Mobil 440 Standard Station, Cematic 3000 12 V Pump, Cover	440	118	80	71	28	39	10988
Le lot de 4 stations Easy Mobil 440 Standard, capot	440				28	156	10988L

1	Forklift Forks Passage
2	2 straps for securing
3	4 vacuum stacking studs
4	Automatic gun with rotating coupling
5	Gun holder
6	Filling cap Ø 56 x 4 mm with relief/ventilation valve
7	12 V self-priming pump, suction with strainer
8	Hose reel for integrated distribution hose
9	Integrated handles for vacuum handling
J	Hazard Prevention Stickers
K ²¹	Optional orange PFV cover
L	Stainless steel lever closure for orange hood

Stickers for the prevention of risks related to the transport of diesel oil

TANK	
Materials used	UV resistant single wall grey polyethylene
Wall thickness	5 mm
Eligible Products	Gasoil, GNR, diesel, fioul
Densité liquide maxi admissible	1,2 kg / dm ³
Operating temperature range	-20° C à +40° C
Anti-roll wall	Yes
Charge/densité maximum	1,2 kg / dm ³
POMPE	
Eligible Products	Gasoil, GNR, diesel, fioul
Débit	45 l/min
Viscosité maxi	De 2 à 5,35 cSt
Maximum pressure	1 bar
Max aspi height	2 m
Sound level	< 70 dB
Tension	12 V
Intensité	22 A
Power	260 W
Maximum speed of rotation	2 600 tr/min
Protection rating	IP55
Maximum cycle time	30 min
Capacité fusible	25 A
Materials used	Pump body in cast iron, steel rotor, acetal resin pallets
Operating temperature range	De -20°C à +60°C
Output input connector	Cannelures 3/4" coudées
Electrical connection	4 m with crocodile clips
Discharge hose	4 meters rubber DN 19
Suction hose	Rubber DN 19
Check valve	Non
Crépine	Yes
Pistolet	Automatic
Counter	Optional
ENSEMBLE	
Circuit breaker valve	Non
Load-handling	Yes
Gerbable	Empty yes
Transportable	Yes
Stockage	On retention