



L
J12
9 6

Designation	Dimensions in cm				Weight en kg	Reference
	a	b	c	d		
Easy Mobil 210 Station, Cematic 12/40 12 V	79	60	69	20	22	10980
The set of 4 stations Easy Mobil 210, Cematic 12/40 12 V					88	10980L
Easy Mobil 210 Station, Cematic 12/40 12 V, Cover	79	60	69	20	24	10983F
The set of 4 stations Easy Mobil 210, Cematic 12/40 12 V, cover					96	10983L

1	Forklift Forks Passage
2	2 straps for securing
3	4 vacuum stacking studs
4	Automatic gun with rotating coupling
5	Gun holder
6	Filling cap Ø 56 x 4 mm with relief/ventilation valve
7	12 V self-priming pump, suction with strainer
8	Hose reel for integrated distribution hose
9	Integrated handles for vacuum handling
J	Stickers for the prevention of risks related to the transport of diesel oil
K	Optional orange PFV cover
L	Stainless steel lever closure for orange hood

TANK	
Materials used	UV resistant single wall grey polyethylene
Wall thickness	5 mm
Eligible Products	Gasoil, GNR, diesel, fioul
Operating temperature range	-20° C à +40° C
Anti-roll wall	Non
Charge/densité maximum	1,2 kg / dm ³
POMPE	
Eligible Products	Gasoil, GNR, diesel, fioul
Débit	40 l/min
Viscosité maxi	De 2 à 5,35 cSt
Maximum pressure	1 bar
Max aspi height	2 m
Sound level	< 70 dB
Tension	12 V
Intensité	18 A
Power	120 W
Maximum speed of rotation	3 800 tr/min
Protection rating	IP55
Maximum cycle time	30 min
Capacité fusible	25 A
Materials used	Pump body in cast iron, steel rotor, acetal resin pallets
Operating temperature range	De -20°c à +60°C
Output input connector	F 3/4' with MF 3/4'-1' reductions
Electrical connection	4 m with crocodile clips
Discharge hose	4 meters rubber DN 19
Suction hose	Rubber DN 19
Check valve	Non
Crépine	Yes
Pistolet	Automatic
Counter	Optional
ENSEMBLE	
Circuit breaker valve	Non
Load-handling	Yes
Gerbable	Empty yes
Transportable	Yes
Stockage	On retention