



# strands®


-lighting division




Part No. 809235  
UNITY WORK LIGHT 10W LED




Part No. 809236  
UNITY WORK LIGHT 19W LED




Part No. 809237  
UNITY WORK LIGHT 31W LED



Part No. 809238  
UNITY WORK LIGHT 64W LED



Part No. 809240  
UNITY WORK LIGHT 92W LED



Part No. 809239  
UNITY WORK LIGHT 149W LED

## UNITY WORK LIGHT LED

LED



PART NO.	809235	809236	809237	809238	809240	809239
VOLTAGE	10-32V DC	10-32V DC	10-40V DC	10-40V DC	10-40V DC	10-40V DC
CONSUMPTION	10W	19W	31W	64W	92W	149W
THEORETICAL LUMEN	1520	3040	2750	6187	15000	21600
ACTUAL LUMEN	1080	1942	2200	5200	7366	13000
IP-CLASS	IP68	IP68	IP67/IP69K	IP67/IP69K	IP67/IP69K	IP67/IP69K
CONNECTION	DT	DT	DT	DT	DT	DT
CABLE LENGTH	500mm	250mm	520mm	520mm	500mm	200mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	52,11mm	-	70,4mm	101mm	110,27mm	135mm
DIAMETER	-	84,4mm	-	-	-	-
DEPTH	26,13mm	54,72mm	41mm	45mm	57,6mm	90,4mm
HEIGHT	67,03mm	-	85,2mm	114,4mm	110,26mm	118mm
HEIGHT INCLUDING BRACKET	112,2mm	112,2mm	95,5mm	120mm	144,13mm	152,2mm
OPERATING TEMPERATURE	-30°C · +65°C	-20°C · +45°C	-20°C · +40°C	-20°C · +40°C	-30°C · 45°C	-20°C · +40°C
E-APPROVED	No	No	No	No	No	No
EMC-CERTIFICATES	ECE R10	ECE R10 CISPR25 Class3	ECE R10	ECE R10	ECE R10	ECE R10