



# strands®


-lighting division




Part No. 908530  
**PRESIDENT 35W RED POSITION LIGHT**




Part No. 908531  
**PRESIDENT 18W**



Part No. 908532  
**PRESIDENT 35W**



Part No. 908533  
**PRESIDENT 35W  
AMBER POSITION LIGHT**



Part No. 908534  
**PRESIDENT 70W**

## PRESIDENT WORK LIGHT LED



PART NO.	908530	908531	908532	908533	908534
VOLTAGE	12-70V DC	12-70V DC	12-70V DC	12-70V DC	12-70V DC
CONSUMPTION	35W	18W	35W	35W	70W
THEORETICAL LUMEN	4512	2460	4512	4512	7100
ACTUAL LUMEN	3000	1750	3000	3000	5400
IP-CLASS	IP67/IP69K	IP67/IP69K	IP67/IP69K	IP67/IP69K	IP67/IP69K
BEAM PATTERN	Flood	Flood	Flood	Flood	Flood
POSITION LIGHT	Yes, red	No	No	Yes, amber	No
CONNECTION	Cable	Cable	Cable	Cable	DT
CABLE LENGTH	2000 mm	2000 mm	2000 mm	2000 mm	2000 mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	109 mm	109 mm	109 mm	109 mm	109 mm
HEIGHT	109 mm	109 mm	109 mm	109 mm	109 mm
DEPTH	49 mm	49 mm	49 mm	49 mm	70 mm
HEIGHT INCLUDING BRACKET	133 mm	133 mm	133 mm	133 mm	133 mm
OPERATING TEMPERATURE	-40°C.+40°C	-40°C.+40°C	-40°C.+40°C	-40°C.+40°C	-40°C.+40°C
E-APPROVED	No	ECE R23	No	No	No
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10